



| | |
|----|----|
| 侧口 | 1" |
| 名称 | 规格 |

| 长度编码 Length Code | L Inch (mm) | P Standard Inch (mm) | 壳体重量 lb (kg) |
|---------------------|----------------|----------------------------|-----------------|
| 1 | 49.53 (1258) | 42 (1067) | 20 (9) |
| 2 | 89.53 (2274) | 82 (2083) | 26 (12) |
| 3 | 129.53 (3290) | 122 (3099) | 35 (16) |
| 4 | 169.53 (4306) | 162 (4115) | 38 (19) |
| 5 | 209.53 (5322) | 202 (5131) | 50 (23) |
| 6 | 249.53 (6338) | 242 (6147) | 57 (26) |

| | | | |
|----|------------------------------------|------|--------------------------|
| 13 | 月牙片Crescent film | 4 | SA-213, 304 |
| 12 | 内六角螺栓Inner hexagonal head bolt | 4 | M6*1 |
| 11 | 钢带护套Steel sheath | 2or3 | 软质PVC Soft PVC |
| 10 | 钢带螺母Steel strip nut | 4or6 | HPB59-1 |
| 9 | 承压头O型圈Pressure head O type ring | 2 | EPDM |
| 8 | 大密封圈Large sealing ring | 2 | EPDM |
| 7 | 产品序列号标签Product serial number label | 1 | 铜版纸Art paper |
| 6 | 侧口 | 2 | 304/316L |
| 5 | 侧口螺母 | 2 | 304/316L |
| 4 | 膜壳标签Shell label | 1 | 不干胶标签Self-adhesive label |
| 3 | 侧口密封圈 | 2 | EPDM |
| 2 | 承压头Pressure head | 2 | PP+30%FG |
| 1 | 壳体Housing | 1 | 环氧+玻纤Epoxy + glass fiber |
| 序号 | 名称 | 数量 | 材料 |

技术要求:

1.膜壳最大压力为: 450PSI(31KG/CM²),

水介质温度: 1℃ ~ 49℃;

不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:

Shell maximum pressure : 450PSI,(31KG/CM²)

Water medium temperature: 1 to 49;

Can not be used in corrosive liquid occasions;

Note: dimensions in brackets refer to dimensions.

| SIGNATURE | | | Winder® 河北成达管业有限公司 HE BEI CHENGDA PIPES CO.,LTD | | |
|--|------|------|--|-------------|------------------------------------|
| | NAME | DATE | | | |
| DESIGN | | | 比例 SCALE | 材料 MATERIAL | 型号 TYPE W40S450 |
| REVIEW | | | 数量 QUANTITY | 光洁度 SMOOTH | 描述 DESCRIPTION MEMBRANE HOUSING |
| THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY | | | 投影 PROJ | 电脑编号 NO. | 图号 DRAWING NO. CD-Z-18 |
| | | | DO NOT MEASURE THE DIMENSIONS. | | |