



- 设计压力6.9MPa(1000PSI)
Design Pressure 6.9MPa(1000PSI)
- 设计温度66℃(150°F)
Design Temperature 66℃(150°F)
- 最低允许温度-10℃(14°F)
Min Temperature -10℃(14°F)
- 工作介质为PH3-10的水
Media:Water PH3-10
- 净水口压力为0.88MPa(125PSI)
0.88MPa(125PSI)
- 项目3数量由客户选择决定;项目5仅在浓水端
The number of items 3 is determined by the customer's choice; Item 5. At the end of concentrated water only
- 图纸仅供参考,具体以实物为准
Drawings are for reference only, in kind
- 请按照说明书正确使用
Please operate it according to operation manual

长度编码 Length	S (mm)	L (mm)	P (mm)	重量 WEIGHT (kg)
1	632 (24.9)	1532 (60.3)	1147 (45.2)	58 (127.6)
2	1648 (64.9)	2548 (100.3)	2163 (85.2)	73 (160.6)
3	2664 (104.9)	3564 (140.3)	3179 (125.2)	88 (193.6)
4	3680 (144.9)	4580 (180.3)	4195 (165.2)	103 (226.6)
5	4696 (184.9)	5596 (220.3)	5211 (205.2)	118 (259.6)
6	5712 (224.9)	6612 (260.3)	6227 (245.2)	133 (292.6)
7	6728 (264.9)	7628 (300.3)	7243 (285.2)	148 (325.6)

18	紧固螺母 FASTENING NUT	2	工程塑料 Engineering Plastic
17	螺栓 BOLT	6	SUS304
16	定位环 POSITIONING RING	2	工程塑料 Engineering Plastic
15	挡块 BLOCK	6	SUS316L
14	嵌入钢圈 EMBEDDED RING	2	SUS316L
12/13	钢带 STRAP+螺丝 screwhead (螺栓尺寸: M8*90)	2-3	A-666, 304+A216
11	鞍座 SADDLE (3芯以上均为3个)	2-3	TPU(S60D)
10	密封板 SEALBOARD	2	ABS
09	适配器 ADAPTOR	2	ABS
08	适配器大/小型圈 ADAPTOR LARGE/SMALL O GLUE	4+4	EPDM 512
07	密封板 O型胶圈 SEALING PLATE O-RING	2	EPDM 512
06	承载板 BEARING PLATE	2	SB-209, 6061-T651
05	止推环 THRUST CONE	1	工程塑料 Engineering Plastic
04	侧口两圈 SIDE DORT	2	SUS304
03	侧口 SIDE PORT	2	SUS316L
02	侧口密封圈 SIDE PORT SEAL RING	4	EPDM 512
01	壳体 SHELL	1	FIBER GLASS +EPOXY

原浓水口规格	D	H
1.5" (DN40)	272	163
2" (DN50)	274	164
2.5" (DN65)	291	171

SIGNATURE		
NAME	DATE	
设计 陈勇	2019.5.13	
审核		
审批		

Winder 河北成达华膜科技有限公司
Hebei Chengda HuaMo Technology Co., Ltd

型号 TYPE W80S1000	单位 UNIT: MM
----------------------------	-----------------------

仅供参考, 零部件以图纸为准, 变更不另行通知

THIS DRAWING CAN NOT BE
USED WITHOUT PRIOR WRITTEN
APPROVAL OF OUR COMPANY